


用途	長さL(mm)	直径D(mm)	軸径d(mm)	表面処理	形名	備考			
鋼製下地のねじ	25	8.0	3.5	ディスコ	SV 3525K2	鋼製下地 (厚さ0.8mm以下)			
	28				SV 3528K2				
	41				SV 3541K2				
ステンレスのねじ	25	8.0	3.9	デュラルコート	SV 3925HD	2×4認定			
	28				SV 3928HD				
	32				SV 3932HD				
	41			SV 3941HD	2×4認定				
	合金鋼のねじ			25	8.0	4.2	ノンクロム	SV 3925HS	2×4認定
				28				SV 3928HS	
				32				SV 3932HS	
				41				SV 3941HS	
				28				SV 4232H(J)	
32		SV 4241H(J)	JIS						
合金鋼のねじ	28	7.0	3.7	ラスパート	SV 3728WF	合板用 フレキねじ			
	32				SV 3732WF				
	41				SV 3741WF				



25 Pcs Belt-type
Precision Improved



25 Pcs Belt-type
Lightweight Strip



25 Pcs Belt-type
Effortless Loading

1. 50 本/連
2. 25 本/連
(新型特許の平テープ)
3. 長さ:16~65 mm
4. ねじ径:M3.5~M4.2



50 Pcs Belt-type



50 Pcs Belt-type



50 Pcs Belt-type



50 Pcs Belt-type

Interference from the chain's dangling tail

Impact the maneuverability and ease of use

5. 50本(1連)連結ビスの平テープは長くて垂れ下がり、施工に干渉され大工さんが困ります。
6. 新型の特許25本(1連)連結ビスを使用することで、施工効率を向上させることができます。